

200S Colloidal Silica Slurry

Resinox Enhanced

Description


Ultra-Sol 200S is a non-drying colloidal silica slurry is designed for polishing precision Opto-Electronic materials such as Silicon, Gallium Arsenide, Indium Phosphide, Germanium, IR materials, and final polish for diamond. Carrying one of our smallest sized colloidal particles, this product can produce excellent finish in both pad and pitch processes.

The Ultra-Sol 200S is a high-purity colloidal silica slurry with a specially designed alkaline dispersion. This reduces problems caused by colloidal particles drying, caking or crystallizing on all exposed surfaces. The end result is an overall reduction in latent scratches, cleaning costs, staining, and waste.

The information provided in this note should be used as a starting point for the customer's application.

Physical Characteristics

SF-200S	
Mean Particle Size	25nm
pH	9.5
Solids Content (By Weight)	25%



Tightly controlled silica particles

Handling

Ultra-Sol 200S is an aqueous based slurry. However, to avoid skin or eye irritation, handlers should use personal protective equipment including, rubber gloves, protective clothing, and eye protection. Follow all MSDS and label precautions and use appropriate industrial safety and hygiene practices when handling or using this product.

It is recommended that Ultra-Sol 200S be used in pure form. However, if desired, it may be diluted up to a 1:1 ratio of using only high-quality de-ionized water (>18 M ohm). Mild agitation is all that is needed to keep the diluted slurry suspended. The product should be mixed periodically 10-20 min/day, by re-circulation or mechanical stirring. Storage and re-use of diluted slurry is not recommended. If diluted slurry is allowed to sit long enough to settle out of suspension, re-use of the settled solids, without proper rework, may cause some minor scratching and should be avoided. Due to the product unique formulation, it is further recommended that the user should not attempt adjustment of the pH. If a different pH is required, please contact your EMINESS Technologies, Inc. Applications Engineer, for assistance in attaining the desired results.

Storage

Storage tanks and distribution piping should be constructed of engineered plastic of polyethylene, polypropylene or fluoropolymer. Materials such as aluminum, copper, brass and PVC should be avoided.

Standard packaging includes five (5) gallon pails and fifty-five (55) gallon drums. One (1) gallon bottles are also available upon request. All containers are High Density Polyethylene (HDPE). Maintain storage in a temperature controlled environment, between 40 and 100°F, avoiding prolonged exposure at either extreme.

Disposal

Dispose in accordance with all applicable regulations.

If you have any questions or comments, please don't hesitate to call your EMINESS Technologies, Inc. Applications Engineer.

About Eminess

For over twenty years Eminess has been providing quality, precision polishing consumables to a vast array of industries. In addition to polishing slurries, Eminess also manufactures a variety of complimentary products, including polishing pads, waxless fixturing, carrier films, and pad conditioners.



We have invested heavily in the tools and infrastructure necessary to provide superior support to our customers, and guarantee quality products through strict observance of ISO 9001 standards. Our knowledgeable support and customer service staff stands ready to assist with polishing projects of any size. For superior products, support, and results, think Eminess!