


Description

Ultra-Sol 3EX is a colloidal silica polishing slurry unique due to its proprietary *neutral* formulation. The 70 nm particle provides excellent removal rates and high quality finishes, while the neutral pH is ideal for polishing applications where corrosion or static etch rates are of concern. Furthermore, the 3EX benefits from having low levels of sodium and other ion contaminants, such as metals and chlorides.

If an acidic or basic colloidal silica is needed, please refer to the other Resinox products, which range in pH from 2.5 up through 11.0.

Physical Characteristics

SF-3EX	
Mean Particle Size	70nm
pH	7.3
Solids Content (By Weight)	30%



Tightly controlled silica particles

Handling

Ultra-Sol 3EX colloidal silica is an aqueous based slurry. However, to avoid skin or eye irritation, handlers should use personal protective equipment including; rubber gloves, protective clothing, and eye protection. Follow all MSDS and label precautions and use appropriate industrial safety and hygiene practices when handling or using this product.

It is recommended that Ultra-Sol 3EX colloidal silica be used in pure form. However, it may be diluted using only high-quality de-ionized water (>18 M ohm). Mild agitation will keep the diluted slurry suspended. The product should be mixed periodically (10 to 20 min/day) by re-circulation or mechanical stirring. If diluted slurry is allowed to sit long enough to settle out of suspension, re-use of the settled solids, without proper rework, may cause some minor scratching and should be avoided. Storage and re-use of diluted slurry is not recommended. Due to the unique formulation, it is further recommended that the user not adjust the pH. If a different pH is required, please contact your EMINESS Technologies, Inc. Applications Engineer, for assistance in attaining the desired results.

Storage

Storage tanks and distribution piping should be constructed of engineered plastic of polyethylene, polypropylene or fluoropolymer. Materials such as aluminum, copper, brass and PVC should be avoided.

Standard packaging includes five (5) gallon pails and fifty-five (55) gallon drums. One (1) gallon bottles are also available upon request. All containers are High Density Polyethylene (HDPE). Maintain storage in a temperature-controlled environment, between 40 and 100°F, avoiding prolonged exposure at either extreme.

Disposal

Dispose in accordance with all applicable regulations.

If you have any questions or comments, please don't hesitate to call your EMINESS Technologies, Inc. Applications Engineer.

About Eminess

For over twenty years Eminess has been providing quality, precision polishing consumables to a vast array of industries. In addition to polishing slurries, Eminess also manufactures a variety of complimentary products, including polishing pads, waxless fixturing, carrier films, and pad conditioners.



We have invested heavily in the tools and infrastructure necessary to provide superior support to our customers, and guarantee quality products through strict observance of ISO 9001 standards. Our knowledgeable support and customer service staff stands ready to assist with polishing projects of any size. For superior products, support, and results, think Eminess!