

Ultra-Sol

C11

Description

Application:

- Polishing oxide films with a requirement to stop on polysilicon or single crystal silicon (Si)
- Minimal removal and no damage to the polysilicon or Si layer
- Works well in unique applications such as MEMS (microelectromechanical systems), optoelectronics, optical coatings, etc.
- Recommended polishing pad:
Rodel IC1000 or IC1000/SIV stacked or IC1000/SP or IC1010/SP pad

Advantages:

- Excellent Surface Finish with no scratching or damage to polysilicon
- Selectivity of 3:1 oxide to polysilicon. (Typical oxide slurries have 1:3 oxide to polysilicon)
- Excellent Removal Rate (RR)

Physical Characteristics

SF-SAP	
Mean Particle Size	
pH	
Solids Content (By Weight)	

Handling

Ultra-Sol C11 is a safe, aqueous based slurry. However, to avoid skin or eye irritation, handlers should use personal protective equipment including; rubber gloves, protective clothing, and eye protection. Follow all MSDS and label precautions and use appropriate industrial safety and hygiene practices when handling or using this product.

It is recommended that Ultra-Sol C11 be used in pure form. However, it may be diluted up to a 1:1 ratio using only high-quality de-ionized water (>18 M ohm). Mild agitation will keep the diluted slurry suspended. The product should be mixed periodically (10 to 20 min/day) by recirculation or mechanical stirring. If diluted slurry is allowed to sit long enough to settle out of suspension, re-use of the settled solids, without proper rework, may cause some minor scratching and should be avoided. Storage and re-use of diluted slurry is not recommended. Due to the unique formulation, it is further recommended that the user not adjust the pH. If a different pH is

required, please contact your EMINESS Technologies, Inc. Applications Engineer, for assistance in attaining the desired results.

Storage

Standard packaging includes five (5) gallon pails and fifty-five (55) gallon drums. One (1) gallon bottles are also available upon request. All containers are High Density Polyethylene (HDPE). Maintain storage in a temperature-controlled environment, between 40 and 100°F, avoiding prolonged exposure at either extreme.

Disposal

Dispose in accordance with all applicable regulations.

If you have any questions or comments, please don't hesitate to call your EMINESS Technologies, Inc. Applications Engineer.

About Eminess

For over twenty years Eminess has been providing quality, precision polishing consumables to a vast array of industries. In addition to polishing slurries, Eminess also manufactures a variety of complimentary products, including polishing pads, waxless fixturing, carrier films, and pad conditioners.



We have invested heavily in the tools and infrastructure necessary to provide superior support to our customers, and guarantee quality products through strict observance of ISO 9001 standards. Our knowledgeable support and customer service staff stands ready to assist with polishing projects of any size. For superior products, support, and results, think Eminess!